

Quality. Innovation. Value.

With over 1,700 thermoforming machines in day-to-day operation, Sencorp brand thermoformers are recognized as the workhorse of the industry. Suitable for forming blister and clamshell packaging for consumer electronics, cosmetics, personal care, medical, and engineered product packaging.



Standard Features

- Free standing material unwind stand
- Form press with 5-inch platen travel (top and bottom)
- Heated sheet-guide
- Servo index
- Cooled rails
- Manual chain-rail adjust

- 100-inch, 30-zone radiant quartz oven
- 115-Ton trim press
- Integrated automatic scrap rewind mechanism
- Siemens control system

Call to learn more 508-771-9400



SPECIFICATIONS

OPTIONS

CONTROLS

Siemens S7 series PLC Electrical: 480V, 3 phase, 60 Hz 15 inch HMI mounted in power panel

FORM PRESS

Area: 31 inches x 36 inches Clamping force: 25 tons Stroke: 5 inches top, 5 inches bottom Shut height: 14 inches - 7 inches top, 7 inches bottom Top shut adjust: +0.125 inches Mold temperature control unit 380V, 3 phase, 50 Hz CE compliance HMI mounted in pendant

25 tons servo press Auto lubrication Forming process control through HMI

Auto X/Y adjust

Auto lubrication

Hydraulic pump for bump cut

Electro mechanical kiss blocks

125 inches length, 44 zone

Heavy duty unwind stand

Max roll diameter: 46 inches

Max roll weight: 2,500 lbs

Lift arms

Sheet sag detection

Closed loop IR sheet scanning

TRIM PRESS

Area: 31 inches x 36 inches (rule die) Cutting force: 115 tons Stroke: 5 inches top, 5 inches bottom Shut height: 6 inches top, 6.188 inches bottom

OVEN

Length: 100 inches Zones: 30 - 15 top, 15 bottom Heating surface: Black faced quartz upper Porcelainized steel faced lower Control: independently retractable

UNWIND STAND

Double roll capacity Max roll diameter: 36 inches Max roll weight: 1,300 lbs

CHAIN RAILS

Sheet width:15.5 inches - 33 inches Web feed: servo driven pin chain Index: 12 inches - 37 inches Index accuracy: +-0.017 inches Automatic chain tensioner Auto chain rail adjust Photo registration

PARTS HANDLING

Stacking/Count/Push off Robot off load system with AB capability Hang hole cleanout

TOOL CHANGEOVER

Quick change master tooling under 1 hour changeover Tool rails 1,000 lbs tool hoist

